



Knee pedals are attached to bottom of underbracing using 5/16-18x3/4" SS Soc. Head Screws

Knee pedals are centered under goosenecks.

Sink Bowl sits flush on top of Frame and is attached with even placed welds

Approval \_\_\_\_\_

Date \_\_\_\_\_



**PROPRIETARY**  
THIS DOCUMENT AND THE DATA DISCLOSED HEREIN OR HERewith IS NOT TO BE REPRODUCED, USED OR OTHERWISE DISCLOSED IN WHOLE OR IN PART TO ANYONE WITHOUT THE WRITTEN AUTHORIZATION FROM G2 AUTOMATED TECHNOLOGIES, LLC

A4

<b>Approvals</b>		<b>Date</b>	
Drawn By J. Lamb		4/7/11	
Approved By N/A		GAT-VERSA-KLEEN-5400-FP-WM	
<b>TITLE</b> SS Hand Sink Manual Floor Valves 4 Stations		<b>Material:</b> SS 304 #3 16 Ga.	
<b>SIZE</b> N/A	<b>CAGE CODE</b>	<b>DWG NO</b> GAT-VERSA-KLEEN-5300-Overall	<b>REV</b>
<b>SCALE</b> Not To Scale		<b>SHEET</b>	